

Jazzy[®] carbon

TRAVEL LITE

With carbon fiber technology, the Jazzy[®] Carbon ultralight power wheelchair becomes your greatest travel companion.



FOLDED DIMENSIONS

height: 28.3"
width: 24"
depth: 12.2"



FDA Class II Medical Device¹

INDEPENDENCE
IN **MOTION**

610-630-8400
www.iimgo.com


JAZZY® CARBON

K0899 POWER MOBILITY DEVICE:

Not coded by DME PDAC or does not meet criteria



FDA Class II Medical Device¹



Military Patches



INDEPENDENCE
IN MOTION™

www.iimgo.com
610-630-8400



AUTHORIZED PROVIDER

FEATURES

- Joystick with built in USB charger is removable for transport
- 24V 12Ah (288WH) airline compliant lithium battery*
- Front suspension for a smooth ride
- Ultra-lightweight, carbon fiber frame specifically designed for traveling
- Compact base easily folds and unfolds for easy transport in a few easy steps
- Padded seat back with storage pocket and soft, removable seat cushion for all-day comfort
- Free-wheel levers easily disengage the brake, allowing this lightweight power chair to be pushed like a manual chair
- Under-seat storage and adjustable lap belt



ACCESSORIES

- Stealth® Simplicity cushion
- Military patches
- Additional battery

SPECIFICATIONS

WEIGHT CAPACITY 300 lbs.

MAXIMUM SPEED² Up to 3.7 mph

DIMENSIONS³ Width: 24" Length: 37"

TOTAL WEIGHT 43.6 lbs. (39.6 lbs. without batteries)

TURNING RADIUS 24"

RANGE PER CHARGE³ Up to 9.3 miles

WARRANTY

FRAME: Lifetime limited

ELECTRICAL CONTROL OR LEVER SYSTEM: 1-year limited

MOTOR/DRIVE SYSTEM: 1-year limited

BEARING AND SHAFT SLEEVE: 1-year limited

BATTERY: 1-year limited

* Transport of this item on commercial aircraft is subject to federal regulations and airline policy. Please consult your airline prior to your flight to ensure your Jazzy® Carbon and its lithium ion battery are permitted.

1. Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
2. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).
3. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

PRIDE®
MOBILITY
LIVE YOUR BEST®