

Buzzaround 3 wheel GB121B-SHZ 4 wheel GB124A-SHZ



Standard Colors:



Red



Blue

Features:

- 325 lb. Weight Capacity
- Comfort Spring Suspension
- Manually Adjustable Preload on Rear Suspension
- Improved Drivability
- Higher Ground Clearance
- LED Angle-adjustable Headlight
- USB Port on the Tiller
- Phone & Cup Holders
- Quick & Easy Disassembly

Upgrade with NEW XR Extended Range Battery Option!

(Packaged separately as an accessory but ships with the unit.)

The next generation of the popular Buzzaround XLSHD features compact portability with a heavy-duty weight capacity! The XLSHD features a robust 325 lb. weight capacity and our Comfort Spring Suspension for a smoother ride. It offers improved standard features like a larger wraparound Delta tiller, higher ground clearance of 4", and an operating range of up to 9 miles on the standard 12 AH batteries. Upgrade with the new XR Extended Range Battery option for even more mileage! The Buzzaround XLSHD also offers a new stylish, contoured stadium style seat for more comfort and increased seating tolerance. This scooter disassembles in seconds with just four easy steps making transporting it from one destination to another a breeze!





610-630-8400 www.iimgo.com





| Item | GB121B-SHZ | GB124A-SHZ |
|---|--------------------|--------------------|
| Description | XLSHD | XLSHD |
| Medicare Code | Not Coded | Not Coded |
| Weight Capacity | 325 lbs. | 325 lbs. |
| Drive Wheels | Rear | Rear |
| Maximum Speed | 4 mph | 4 mph |
| Operating Range up to ¹ | 9 miles/18 miles | 9 miles/18 miles |
| Under Deck Clearance | 4" | 4" |
| Turning Radius | 37.5" | 44" |
| Type Batteries | 2-12 AH / 2-22 AH | 2-12 AH / 2-22 AH |
| Colors | Red, Blue | Red, Blue |
| Freewheel Mode | Yes | Yes |
| Electronic Speed Control | Yes | Yes |
| Electro-Mechanical Brakes | Yes | Yes |
| Charger | Off-board | Off-board |
| Controller | 50 Amp | 50 Amp |
| Dimensions | | |
| Length | 41" | 40" |
| Width | 20" | 20" |
| Height (ground to top of back of seat) | 34.25"-35.75" | 34.25"-35.75" |
| Ground to Top of Seat | 22.25"-23.75" | 22.25"-23.75" |
| Ground to Top of Deck | 5.5" | 5.5" |
| Deck to Top of Seat | 16.5"-18" | 16.5"-18" |
| Number of Seat Height Pos | | 3 |
| Size of Increments | .75" | .75" |
| Front Axle to Rear Axle | 31.5" | 30.5" |
| Weight of Unit: (assembled) ³ | 100 lbs. | 105 lbs. |
| Front Half | 35 lbs. | 40 lbs. |
| Rear Half | 28 lbs. | 28 lbs. |
| Seat w/Arms | 21 lbs. | 21 lbs. |
| Batteries | 16 lbs. / 30 lbs. | 16 lbs. / 30 lbs. |
| Tires: | Solid, low profile | Solid, low profile |
| Front | 7.5" | 7.5" |
| Rear | 8" | 8" |
| Rear Anti-Tip Wheels | 2" | 2" |
| Standard Seat | Stadium Style | Stadium Style |
| Seat Back Height - no headrest | 14.75" | 14.75" |
| Width x Depth | 17" x 14.5" | 17" x 14.5" |
| Color | Black Vinyl | Black Vinyl |
| Warranty: | | |
| Frame | Lifetime Warranty | Lifetime Warranty |
| Drive Train | 2 Year Warranty | 2 Year Warranty |
| Electronics ² | 2 Year Warranty | 2 Year Warranty |
| Batteries | 1 Year Warranty | 1 Year Warranty |
| 24(6)165 | 1 Tour Warranty | 1 Tour Warranty |

Battery range at 200 lbs. and will vary due to rider weight, drive surface, terrain, and battery type.

^{2.} Electronics warranty excludes batteries.







Disassembles into 5 Pieces!

3 Wheel Model Shown



Comfort Spring Suspension Manually adjustable preload on rear suspension!



610-630-8400 www.iimgo.com