| Group 2: Heavy Duty (K0824/K0825) |
|---|
| Group 2. Fleavy Duty (R0024/R0023) |
| 450 lbs. |
| 22" |
| 25.4" |
| 40.5" |
| Up to 4.88 mph |
| 3" |
| 6" |
| 13.75" perforated |
| 6" |
| Two in-line HD motors |
| Regenerative and electromechanical |
| Full independent front and rear Active-Trac® ATX Suspension |
| 18" x 18-20" 20" x 18-20" 22" x 20-22" |
| 22-24" |
| Up to 13 miles at 450 lbs. Up to 21.5 miles at 200 lbs. |
| 60A Dynamic Linx |
| Base: 125.7 lbs. Seat: 57.8 lbs. Batteries: (2) 36 lbs. each; |
| 255.5 lbs. |
| (2) NF-22 |
| 5 amp, off-board |
| Frame: 5-year limited Drivetrain: 13-month limited Electronics: 13-month limited Battery: 13-month limited |
| |

- 1 Pride® FDA Class II Medical Devices are designed to aid individuals with mobility impairments.
- 2 Varies with user weight, terrain, battery type, battery condition and tire pressure. 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).
- 4 Total weight includes base, seat and batteries.
- 5 Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.
- 6 Battery weight may vary based on manufacturer.



www.iimgo.com 610-630-8400





www.iimgo.com/jazzy-evo-614hd

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

The information contained herein is correct at time of publication; we reserve the right to alter specifications without prior notice.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or -3 %. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.





The Future of Heavy Duty Mobility

The Jazzy® EVO 614HD has tall 13.75-inch drive wheels, the centerpiece for Pride's beloved Mid-Wheel 6® platform. Active-Trac® ATX Suspension adapts to the terrain, so grassy fields and gravel paths feel smoother than they ever have before. And now, with a new memory foam seat, your Jazzy EVO 614HD is ready to provide all-day comfort right out of the box.

- 3" ground clearance
- 13.75" perforated mid-wheel drive tires
- Front and rear independent Active-Trac® ATX Suspension
- Removable matte-finish color-through shrouds
- Depth-adjustable, limited recline, memory foam heavy duty single seat post allows the user to swivel
- Access to controller and batteries without the user needing to exit the chair
- Standard lap belt (60" 18" or 20" W, 70" 20" W)

Available Colors



Accessories

- Cane/crutch holder
- Cell phone holder
- Cup holder
- Flag kit
- Oxygen tank holder
- Rear basket
- Saddlebag
- Stealth® cushions
- Walker holder
- Weather cover
- 2.1A XLR USB charger
- 50-90" lap belts

Options

- Elevated leg rests
- Solid seat pan, limited recline, high-back with swivel
- Heel loops
- Swing-away joystick
- Swing-away leg rests
- Unoccupied transit
- Residual limb support

Military Patches

