

Aluminum Tilt Shower Commode Chair 18" Seat

The aluminum attendant shower and commode chair is a tilting back 18" seat commode and a transport chair in one. The chair comes with four 5" locking casters to provide safety when the user does not need to be moved. The seat cut-out provides comfort and allows the chair to be positioned over a standard toilet for use, but also comes with a bucket to be used anywhere it is required. The aluminum frame of the Shower Commode Chair is an attractive white color and is also resistant to rust which makes it ideal for the shower. Footrests come standard and include adjustable height and angle footplates. The Aluminum Shower Commode Chair is ideal for anyone who is looking for a shower chair and commode for their home.

Features

- Can be positioned over a standard toilet or used as a portable self contained commode.
- Floor to seat height can be adjusted 4" without tools
- White aluminum frame is attractive and rust resistant
- Padded seat back and arms.
- Height adjustable.
- Comes with swing-away footrests.
- Slide on pail, removable
- Flip back arms
- Maintenance free tires
- Calf Strap included
- Molded handrims
- Super soft seat
- Easier rolling
- Seat Belt
- Optional 24" wheels



INDEPENDENCE
IN MOTION™

www.iimgo.com
610-630-8400



Aluminum Tilt Shower Commode Chair

SPECIFICATIONS

Frame Material	Aluminum
Weight Capacity	300 lbs.
Rear Wheels	5" Locking Casters
Optional Rear Wheels	24"
Seat Width	18"
Seat Depth	17"
Foot Rest Hanger Angle	60 degrees
Foot Rest Length	14" to 20"
Back Height	18"
Product Weight	36 lbs.
Arm Height	11" (from seat)
Arm Length	13"
Arm Pad Length	9"
Tilt Range Posterior	20 degrees
Rear Internal Width	15"
Seat Heights (Standard)	21", 22" or 23"
Seat Heights (Tall)	22.9", 23.9", 24.9"
Seat Clearance Height	19", 20", 21"
Seat Clearance Height	21", 22", 23"

Dimensions with 5" Rear Casters:

Overall Width	22"
Overall Length	40"

Dimensions with 24" Rear Wheels:

Overall Width	26"
Overall Length	45"



INDEPENDENCE
IN MOTION™

www.iimgo.com
610-630-8400

